



PRODUCT SHEET

European Oak Collection (180mm), BHRL-008

Product Features

TYPE:	Two-layer wood floor with protective finish
PRODUCTION:	Finished by BoardHouse in Los Angeles, CA, USA
WEAR LAYER:	Solid wood wear layer approximately 6mm thick
SUPPORT:	Phenolic multilayer Birch support with tangled fibers, 14mm thick, FSC Certified
JOINTS:	Each plank has a tongue on the top and right edges and a groove on the lower and left edges
LENGTHS:	Planks are random lengths approximately 6' to 8' with 10%-15% shorter lengths developing; Average Lengths 6' 3" -6'11"
WIDTH:	Planks are 7" (180mm) wide
OVERALL THICKNESS:	Overall Thickness is 3/4" (20mm)
OTHER FEATURES:	1/32" overall micro bevel
SURFACE TEXTURE:	Brushed

Wood Specie and Grade

WOOD SPECIES	GRADE	HARDNESS	STABILITY	OXIDATION
European Oak Quercus pedunculata, O. Robur	Prime Flat Sawn, healthy pin knots up to 10mm, no sap	Medium-High	Medium-High	High
	Classic Live Sawn, healthy knots up to 50-60 mm, sap allowance 1%-10%, knots filled, all knots are small and not open. Black knots up to 25mm			
The wood colors mainly depend on the wood species and finish. Each wood color varies when exposed to light for period of time (oxidation). Each wood species has its own color and texture. Each wood species and lot shows a different look depending on the area of origin. Prime, Classic, and Custom grades are in conformity with the features described in the Free Grade Chart.				



Finish and Maintenance

Glitsa Gold Seal Urethane	Swedish formulated Gold Seal Finishes have been the benchmark of excellence that no other finish has matched. The Gold Seal System provides a unique combination of durability, scratch and scuff resistance, clarity, and grain definition. The Gold Seal System also provides unsurpassed beauty by bringing out the natural colors of your wood floor.
Maintenance	See provided Care and Maintenance Instructions We recommend Glitsa Clean or Bona Hardwood Floor Cleaner (both available in ready-to-use spray bottles). In addition, BoardHouse will supply private label urethane cleaner in ready-to-use spray bottles.

Certificates

	
BoardHouse products are in conformity with UNI EN 14342:2005 + A1:2008 regulations.	FSC trademark identifies products made with wood from forests managed in a correct and responsible way in accordance with strict environmental, social, and economic standards. BoardHouse's supplier of European Oak platform supplies FSC Certified wood and platform, Cert #SGS-COC-002143. BoardHouse is not an FSC Certified Organization.

Installation

GLUED INSTALLATION	BoardHouse recommends Mastic
FLOATING INSTALATION	Not allowed
HEATED SUBFLOORS	The floor can be installed via glue down on heated sub floors